WHAT IS CLAIMED IS:

1   1. An electronic equipment which is used while being connected to

2 a display device, said electronic equipment comprising:

3   a receiving part which receives input signals from N pieces (N $\geq$

4 2) of pointing devices; and

5   a pointer control part which decides respective display positions

6 of N pieces of pointers displayed on said display device based on input

7 signals which said receiving part receives.

1   2. An electronic equipment which is used while being connected to

2 a display device, said electronic equipment comprising:

3   a first receiving part which receives a first input signal from a first

4 pointing device;

5   a second receiving part which receives a second input signal from

6 a second pointing device;

7   a first pointer control part which decides a display position of a

8 first pointer displayed on said display device based on said first input

9 signal which said first receiving part receives; and

10   a second pointer control part which decides a display position of a

11 second pointer displayed on said display device based on said second

12 input signal which said second receiving part receives.

1   3. An electronic equipment according to claim 2, said electronic

12

2   equipment further comprising:

3   a display content decision part which decides the display content

4   of said display device in response to said first input signal, said second

5   input signal, information indicative of the display position of said first

6   pointer and information indicative of the display position of said second

7   pointer.

1   4. A method for deciding the display position of a pointer, said

2   method comprising the steps of:

3   receiving a first input signal from a first pointing device;

4   deciding the display position of a first pointer displayed on a

5   display device based on said first input signal;

6   receiving a second input signal from a second pointing device; and

7   deciding the display position of a second pointer displayed on said

8   display device based on said second input signal.

1   5. A storage medium for recording a program, which is executed

2   on a computer, said program comprising the steps of:

3   receiving a first input signal from a first pointing device;

4   fixing a position of a first pointer, which is displayed onto a

5   display device, by calculating said first input signal;

6   receiving a second input signal from a second pointing device; and

7   fixing a position of a second pointer, which is displayed onto a

8   display device, by calculating said second input signal.

1   6. A program for making a computer execute following processing

2   which comprises:

3   processing which receives a first input signal from a first pointing

4   device and decides the display position of a first pointer displayed on a

5   display device based on said first input signal; and

6   processing which receives a second input signal from a second

7   pointing device and decides the display position of a second pointer

8   displayed on said display device based on said second input signal.

1   7. An electronic equipment comprising:

2   a first connecting part for connecting said electronic equipment to

3   a display device;

4   a second connecting part for connecting said electronic equipment

5   to a first pointing device;

6   a third connecting part for connecting said electronic equipment to

7   a second pointing device; and

8   a display control part which displays, when said display device is

9   connected to said first connecting part, a first pointer which is displaced

10   based on an instruction from said first pointing device which is connected

11   to said second connecting part and a second pointer which is displaced

12   based on an instruction from said second pointing device which is

13   connected to said third connecting part on said display device.

1   8. An electronic equipment according to claim 7, said electronic

2   equipment further comprising:

3   a processing part which specifies a position which becomes the

4   reference or an object which becomes a subject on a display screen of said

14

5   display device based on either one of said instructions of said first and

6   second pointing devices, and decides the content of a manipulation to said

7   position which becomes the reference or said object which becomes the

8   subject based on the other instruction.